



# Samsung Mono Laser Printer ML-3310ND/ML-3710ND



## Key Features:

- Print Speeds up to 31ppm/35ppm in A4
- First Print Out Time 6.5 seconds (from Ready Mode)
- Improved Print Quality with up to 1,200 x 1,200dpi
- Maximum Monthly Duty Cycle 50,000/80,000 sheets
- Quiet Operation at less than 51/52dBA (printing)
- Standard Cartridge Yield of 2,000/5,000 pages
- 250-sheet Standard Input Capacity, 50-sheet Multi-Purpose Tray

## The office printer that demands less yet delivers more.

When you choose a printer for your business – you want to know that you’re making the right choice. You want a printer that not only provides exceptional print quality – but delivers value too. Because the Samsung ML-3310ND/ML-3710ND are so simple to use, they do just that. Simple menu structures mean everyone can utilise all the features it has to offer. Simple paper handling means that you can print on a wide range of papers and card stock – delivering professional results every time. Simple technology keeps paper jams at bay – and your teams focused on their jobs.

Easy to use and maintain, the Samsung ML-3310ND/ML-3710ND effortlessly combines high performance with outstanding productivity and versatility. Perfect for the busy office - perfect for you.

## Top 3 Reasons to Buy:

- 1 Easy to Use and Maintain:**
  - LEDs for at a glance status updates and simple navigation
  - Improved paper feed technology to prevent unwanted multiple page paper pickups.
- 2 Economical Performance:**
  - Switch to toner save mode at the touch of a button
  - Lower cost per page and fewer toner replacements with extra high yield toner cartridges.
- 3 Straightforward Productivity:**
  - 820 sheet total paper capacity for minimal paper refills
  - 600MHz dual-core processor for fast, productive output
  - Fast printout speeds of up to 31ppm/35ppm across the range.

## Product Configuration



## Product Datasheet

# Samsung Mono Laser Printer ML-3310ND/3710ND

## Product Specifications

	ML-3310ND	ML-3710ND
<b>Overview</b>		
Function	Print	
Value	Eco Button	
Added Function	-	
<b>Print</b>		
Speed (Mono)	Up to 31ppm in A4 (33ppm in Letter)	Up to 35ppm in A4 (37ppm in Letter)
Resolution	Up to 1,200 x 1,200dpi effective output	
First Print Out Time (Mono)	6.5 seconds	
Emulation	PCL5e, SPL, IBM ProPrinter, EPSON	PostScript3, PCL6/5e, IBM ProPrinter, EPSON
Duplex	Built-in	
<b>Paper Handling</b>		
Input Capacity and Types	250-sheet Cassette, Manual feeder, 250-sheet Cassette, 50-sheet Multi-Purpose Tray	
Output Capacity and Type	150-sheet Face-Down, 1-sheet Face-Up	
Media Size	76 x 127mm (3" x 5") ~ 216 x 356mm (8.5" x 14")	
Media Type	Plain, Thin, Thick, Thicker, Cotton, Coloured, Envelope, Transparency, Pre-Printed, Recycled, Labels, Bond, Card stock, Archive	
Envelope Capacity	5 sheets	
<b>General</b>		
Processor	Samsung 375MHz	Samsung 600MHz
Memory/Storage	64MB	128MB (Max. 384MB)
OS Compatibility	Microsoft Windows: 2000/XP (32/64 bit), Vista (32/64 bit), 2003 Server (32/64 bit), 2008 Server (32/64 bit), Windows 7 (32/64 bit), 2008 Server R2 (64 bit); Various Linux OS: RedHat Enterprise Linux WS 4, 5 (32/64 bit), Fedora 4 to 12 (32/64 bit), SuSE Linux 10.0, 10.1 (32 bit), OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit), Mandriva 2005 to 2009.1 (32/64 bit), Ubuntu 5.04, 5.10, 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10 (32/64 bit), SuSE Linux Enterprise Desktop 10, 11 (32/64 bit), Debian 4.0, 5.0 (32/64 bit); Mac OS 10.3 ~ 10.6.	Microsoft Windows: 2000/XP (32/64 bit), Vista (32/64 bit), 2003 Server (32/64 bit), 2008 Server (32/64 bit), Windows 7 (32/64 bit), 2008 Server R2 (64 bit); Various Linux OS: RedHat Enterprise Linux WS 4, 5 (32/64 bit), Fedora 4 to 12 (32/64 bit), SuSE Linux 10.0, 10.1 (32 bit), OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit), Mandriva 2005 to 2009.1 (32/64 bit), Ubuntu 5.04, 5.10, 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10 (32/64 bit), SuSE Linux Enterprise Desktop 10, 11 (32/64 bit), Debian 4.0, 5.0 (32/64 bit); Mac OS 10.3 ~ 10.6; UNIX OS: Sun Solaris 9, 10 (x86, SPARC); HP-UX 11.0, 11i v1, 11i v2, 11i v3 (PA-RISC, Itanium) and IBM AIX 5.1, 5.2, 5.3, 5.4.
Interface	Hi-Speed USB 2.0	Hi-Speed USB 2.0, Ethernet 10/100/1000 Base TX
Noise Level	Less than 51dBA (Printing), Background Noise Only - Less than 26dBA (Standby)	Less than 52dBA (Printing), Background Noise Only - Less than 26dBA (Standby)
Duty Cycle, Monthly	50,000 sheets	80,000 sheets
Dimension (WxDxH)	366 x 368 x 252.9mm	
Weight	9.74Kg	9.95Kg
Power Consumption	3.5W/60W/550W	3.5W/60W/600W

<b>Consumables</b>		
Yield	Standard: Average Cartridge Yield 2,000 standard pages. High Yield: Average Cartridge Yield 5,000 standard pages. Ships with 2,000 pages Starter Toner Cartridge, Declared Cartridge Yield in accordance with ISO/IEC 19752.	Standard: Average Cartridge Yield 2,000 standard pages. High Yield: Average Cartridge Yield 5,000 standard pages. Extra High yield: Average Cartridge yield 10,000 standard pages. Ships with 5,000 pages Starter Toner Cartridge. Declared Cartridge Yield in accordance with ISO/IEC 19752.
Type	1-piece Cartridge	
Codes	MLT-D205S/ELS - 2,000 Pages, MLT-D205L/ELS - 5,000 Pages	MLT-D205S/ELS - 2,000 Pages, MLT-D205L/ELS - 5,000 Pages, MLT-D205E/ELS - 10,000 Pages
<b>Options</b>		
Options	- 520-sheet Cassette Tray - ML-S3710A/SEE - IEEE 1284B Parallel Connector - ML-PAR100/SEE	- 520-sheet Cassette Tray - ML-S3050A/SEE - Memory (256MB) - CLP-MEM202/SEE - IEEE 1284B Parallel Connector - ML-PAR100/SEE



For more information, please visit [www.samsung.com/uk/printer](http://www.samsung.com/uk/printer)

